

INDUSTRIAL SOLUTIONS
A.P.P.S

AEROSPACE / INDUSTRIAL
BIOPHARMACEUTICAL
BIOTECHNOLOGY
MEDICAL DEVICE
PHARMACEUTICAL

BIOCLEAN CLEARVIEW

Autoclavable Goggles

BCAG



BIOCLEAN CLEARVIEW

Autoclavable Goggles

BCAG

About

BioClean Clearview™ Autoclavable Cleanroom Goggles have a super-soft thermoplastic rubber frame with upper and indirect lower ventilation system to provide exceptional wearer comfort. These goggles feature a toughened anti-scratch polycarbonate lens with propriety anti-fog technology for unrivalled clear vision. Provided non-sterile. To be autoclaved at 121°C/250°F for 30 minutes.

Features

- Anti-fog for up-to 20 autoclave cycles
- Super-soft thermoplastic rubber frame
- Upper vents and lower indirect ventilation system
- Toughened polycarbonate, anti-fog, anti-scratch & optically correct lens
- Non-linting latex-free head band
- Tested to withstand >40 autoclave cycles of 30 minutes duration at 121°C/250°F
- Can be worn over eye-glasses

BIOCLEAR CLEARVIEW

Autoclavable Goggles

BCAG

Specification

MATERIAL

Thermoplastic rubber frame, toughened polycarbonate lens, latex-free silicone head band with polypropylene hooks

COLOUR

White frame and black strap

CLASSIFICATION

EN 166:2001 Optical Class 1

COMPATIBILITY

ISO Class 4 & EU GMP Grade A

STERILIZATION

Provided non-sterile. To be autoclaved at 121°C/250°F for 30 minutes



BIOCLEAN CLEARVIEW

Autoclavable Goggles

BCAG

Quality standards

- Manufactured in a facility holding ISO 9001:2008 and 89/686/EEC Article 11 b certifications
- Processed in an NEBB certified ISO Class 4 cleanroom environment
- Conforms to Category 2 - Personal Protective Equipment PPE Directive 89/686/EEC
- Complies with requirements of EN 166:2001 standard for personal eye protection

Shelf life & storage

Five (5) years from date of manufacture. Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

BIOCLEAN CLEARVIEW

Autoclavable Goggles

BCAG

PHISICAL PROPERTIES

Total Weight (2g)	103 g
Lens Tickness (0.3mm)	3.1 mm
Brige width (0.5mm)	70 mm
Bridge height	26 mm
Overall width (hinge to hinge) (3mm)	190mm
Overall Height (3mm)	85 mm

EXPLANATION OF MARKINGS

REQUIRED MARKINGS	MARKINGS ON FRAME	MEANNING
Manufacturer's Identification mark	BioClean	BioClean™
Standard Number	EN166	European Standard on Personal Eye Protection
Field of Use	BT	Medium energy impact at extremes of temperature
Optical Class	1	High optical quality
Conformity Mark	CE	Conformity with European Standards

Packing

Google (BCAG)

One piece per sealed PE bag (to be removed prior to autoclaving); 12 bags per inner box; five boxes per lined carton (60 pieces).

PLEASE NOTE: Product sold per inner box (12 pieces). Provided non-sterile. To be autoclaved at 121°C/250°F for 30 minutes.

BIOCLEAR CLEARVIEW

Autoclavable Googles

BCAG

Contact information

Quotes and orders from around the world

APPS INC.

appsindustrial.com

+1 (818) 930 0779

[Toll free]: +1 818-5743-345

contact@appsindustrial.com

