

# ISO ARK CONTAINMENT SOLUTION

Portable negative pressure  
isolation chamber



## ISO ARK

### CONTAINMENT SOLUTION

Portable negative pressure  
isolation chamber

## Technical information

MODEL	LENGTH (m)	WIDTH (m)	HEIGHT (m)	LENGTH W/ AIRLOCK DOORS OPEN (m)	WEIGHT (Kg)
60X90	1.60	2.35	2.35	3.95	33.50
90X90	2.35	2.35	2.35	3.95	50.00
90X120	3.10	2.35	2.35	4.70	67.00
120X120	3.10	3.10	2.35	4.70	89.00
120X150	3.85	3.10	2.35	5.45	111.00

## ISO ARK

### CONTAINMENT SOLUTION

Portable negative pressure  
isolation chamber

## Technical information

### Antechamber/airlock features

LENGTH (m)	WIDTH (m)	HEIGHT (m)	WEIGHT (Kg)
0.9	1.6	2.1	54

### Shipping containers

	LENGTH (m)	WIDTH (m)	HEIGHT (m)	WEIGHT (Kg)
CHAMBER & ANTECHAMBER	2.31	0.74	1.14	168
FILTRATION SYSTEM TRANSPORT BOX	0.77	0.74	1.15	56

## ISO ARK

### CONTAINMENT SOLUTION

Portable negative pressure  
isolation chamber

# Filtration system performance

3 LEVELS OF AIR FLOW:  
1000/1400/2200 Unit m<sup>3</sup>/h

INTERNAL NEGATIVE PRESSURE:  
Value 8/10/50 Unit Pascal

RUMOR LEVELS:  
Value 52/56/65 Unit dB

FILTRATION EFFICIENCY  
(PARTICULAR DIAMETER @ 0.35) VALUE:  
99.995 / Unit @

CONSUMPTION:  
Value 500/600 / Unit Watt

CERTIFICATIONS:

- AQAP 2110
- ISO 9001
- MIL-satandars
- EN 1822 IEST-PR-CC001.3.

## ISO ARK

## CONTAINMENT SOLUTION

Portable negative pressure  
isolation chamber

# Contact information

Quotes and orders from around the world

APPS INC.

[appsindustrial.com](http://appsindustrial.com)

+1 (818) 930 0779

[Toll free]: +1 818-5743-345

[contact@appsindustrial.com](mailto:contact@appsindustrial.com)

