

INDUSTRIAL SOLUTIONS
A.P.P.S

AEROSPACE / INDUSTRIAL
BIOPHARMACEUTICAL
BIOTECHNOLOGY
MEDICAL DEVICE
PHARMACEUTICAL

BIOCLEAN CLEARVIEW

Autoclavable Goggles

BCAG

Industrial | Life Sciences | Personal protection



BIOCLEAR CLEARVIEW Autoclavable Goggles BCAG

About

BioClean Clearview™ Autoclavable Cleanroom Goggles have a super-soft thermoplastic rubber frame with upper and indirect lower ventilation system to provide exceptional wearer comfort. These goggles feature a toughened anti-scratch polycarbonate lens with propriety anti-fog technology for unrivalled clear vision. Provided non-sterile. To be autoclaved at 121°C/250°F for 30 minutes.

Features

- Anti-fog for up-to 20 autoclave cycles
- Super-soft thermoplastic rubber frame
- Upper vents and lower indirect ventilation system
- Toughened polycarbonate, anti-fog, anti-scratch & optically correct lens
- Non-linting latex-free head band
- Tested to withstand >40 autoclave cycles of 30 minutes duration at 121°C/250°F
- Can be worn over eye-glasses

BIOCLEAN CLEARVIEW Autoclavable Goggles BCAG

Specification

MATERIAL

Thermoplastic rubber frame, toughened polycarbonate lens, latex-free silicone head band with polypropylene hooks

COLOUR

White frame and black strap

CLASSIFICATION

EN 166:2001 Optical Class 1

COMPATIBILITY

ISO Class 4 & EU GMP Grade A

STERILIZATION

Provided non-sterile. To be autoclaved at 121°C/250°F for 30 minutes



BIOCLEAR CLEARVIEW

Autoclavable Goggles

BCAG

Quality standards

- Manufactured in a facility holding ISO 9001:2008 and 89/686/EEC Article 11 b certifications
- Processed in an NEBB certified ISO Class 4 cleanroom environment
- Conforms to Category 2 - Personal Protective Equipment PPE Directive 89/686/EEC
- Complies with requirements of EN 166:2001 standard for personal eye protection

Shelf life & storage

Five (5) years from date of manufacture. Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

BIOCLEAN CLEARVIEW

Autoclavable Goggles

BCAG

PHISICAL PROPERTIES

| | |
|---------------------------------------|--------|
| Total Weight (2g) | 103 g |
| Lens Tickness (0.3mm) | 3.1 mm |
| Brige width (0.5mm) | 70 mm |
| Bridge height | 26 mm |
| Overall width (hinge to hinge) (3mm) | 190mm |
| Overall Height (3mm) | 85 mm |

EXPLANATION OF MARKINGS

| REQUIRED MARKINGS | MARKINGS ON FRAME | MEANNING |
|------------------------------------|-------------------|---|
| Manufacturer's Identification mark | BioClean | BioClean™ |
| Standard Number | EN166 | European Standard on Personal Eye Protection |
| Field of Use | BT | Medium energy impact at extremes of temperature |
| Optical Class | 1 | High optical quality |
| Conformity Mark | CE | Conformity with European Standards |

Packing

Goggle (BCAG)

One piece per sealed PE bag (to be removed prior to autoclaving); 12 bags per inner box; five boxes per lined carton (60 pieces).

PLEASE NOTE: Product sold per inner box (12 pieces).
Provided non-sterile. To be autoclaved at
121°C/250°F for 30 minutes.

BIOCLEAR CLEARVIEW
Autoclavable Goggles
BCAG

Contact information

Quotes and orders from around the world

APPS INC.
appsindustrial.com
+1 (818) 930 0779
[Toll free]: +1 818-5743-345
contact@appsindustrial.com

